

# Pilot Valve for Diesel Engines

Seitz offers an individually optimised Pilot Valve for starting systems of two stroke engines. This pilot valve controls the Start Valve of each cylinder individually and supports the slow turn function as well.



Pilot Valve

## Pilot Valve

### Technical data

<b>Media</b>	Compressed air according ISO 8573.1 – Particles: Quality 5 – Pressure of dew point: Quality 5 – Oil content: Quality 3
<b>Ambient temperature</b>	-20 °C ... +65 °C
<b>Leakage</b>	External: Bubble free Internal: <0.12 NI/h
<b>Material</b>	Valve body: Aluminium anodised Piston: Brass Seals: FPM (Viton)
<b>Mounting position</b>	Arbitrary

## Order information

Valve type	603/41
Seitz Art.-No.	123.211.00
Function	5/2-way Pneumatic Valve
Dimension L × W × H	122 × 61 × 88.5 mm
Operating pressure	0 ... 40 bar
Pilot operation	External medium ≥ P min. 2 bar
DN	10 mm
Connection	Port no. 1,2,3,4,5: Flange Port no. 8: G1/4"
Flow rate	Kv 2.3 m <sup>3</sup> /h

For detailed dimensional drawing or 3-D model, please contact us.

**Eugen Seitz AG**  
Spitalstrasse 204  
8623 Wetzikon  
Switzerland  
**+41 44 931 80 80**  
**info@seitz.ch**

**Seitz Valve Technology (Shanghai) Co., Ltd.**  
Room 910, Building No 67  
Hong Cao Rd 421  
200233 Shanghai  
People's Republic of China  
**+86 21 3363 3880**  
**information@seitz.cn**